

	<h2>Product Data Sheet</h2>
	<p>Celcore HS Rheology Modifying Admixture for Cellular Insulating Concrete</p>

Product Description:

Celcore HS Rheology Modifying Admixture is a proprietary compound specifically formulated to be used in conjunction with **Celcore MF Foam Concentrate**. This product improves the pumpability, flowability and workability of fresh **Celcore MF Cellular Concrete**. The product further improves the hardened properties of the concrete by increasing bond and compressive strength.

Advantages:

- Allows mix water reduction
- Reduces pipeline friction
- Improves plastic workability
- Increases substrate bond strength
- Increases compressive strength

Dosage:

Dosage rates may vary depending upon cement source. Generally, the recommended dosage rate is within a range from 3 - 8 fl/ozs [90 - 240 mls] per 100 lbs [45 kg] of cement.

Directions For Use:

Celcore HS Rheology Modifying Admixture is added to the mix water during the mixing process.

Packaging:

Celcore HS Rheology Modifying Admixture is supplied in (5) gallon [18.9 L] pails, (55) gallon [208.2 L] drums or (250) gallon [946.4 L] totes.

Celcore HS Rheology Modifying Admixture should be protected from freezing. If frozen, some re-mixing may be required.

Applicable Standards:

Celcore HS Rheology Modifying Admixture meets or exceed ASTM C 494, Types A and F.

CAUTIONS:

Always wear proper eye protection as splash possibility exists. Not to be consumed internally. Wash from skin using soap and water. MSDS available upon request by contacting:

CELCORE INCORPORATED
3148 US HWY 70 WEST
BLACK MOUNTAIN, NC 28711
(828) 669-4875
(828) 669-4874 Fax
www.celcoreinc.com